



LOCKING

Stone 1





Stone 1

25 YEAR
GUARANTEE
DOMESTIC

10 YEAR
GUARANTEE
COMMERCIAL

Embossing: Satin / **Thickness:** 5.00mm / **Wear Layer:** 0.55mm / **Coating:** Ceramic Bead /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.



Sandstone Oyster - 48813



Sandstone Midnight - 48818



New Marble Crema - 46415



New Marble Grey - 46413



Stone 1

25 YEAR
GUARANTEE
DOMESTIC

10 YEAR
GUARANTEE
COMMERCIAL

Embossing: Satin / **Thickness:** 5.00mm / **Wear Layer:** 0.55mm / **Coating:** Ceramic Bead /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.



Carrara White - 46513



Carrara Oyster - 46514



Aegean Travertine Ivory - 742915



Aegean Travertine Noche - 742917



Stone 1

25 YEAR
GUARANTEE
DOMESTIC

10 YEAR
GUARANTEE
COMMERCIAL

Embossing: Satin / **Thickness:** 5.00mm / **Wear Layer:** 0.55mm / **Coating:** Ceramic Bead /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.



Aegean Travertine White - 742913



Sandstone Steel - 48817

Stone 1



Espana Cadiz - 35713



Espana Toledo - 35711




Stone 1

25 YEAR
GUARANTEE
DOMESTIC

10 YEAR
GUARANTEE
COMMERCIAL

Embossing: Satin / **Thickness:** 5.00mm / **Wear Layer:** 0.55mm / **Coating:** Ceramic Bead /
Utilization Class: 33/42 / Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. EasyLock itself can be completely recycled.



allure [®] LOCKING		Stone 1		
Thickness (mm)	5.00	Impact Sound Insulation	ISO 717-2	5 dB
Wear Layer (mm)	0.55	Chemical Resistance	EN 423	High Resistance
Utilization Class		Residual Indentation	EN 433	≤ 0,08 mm
Coating	PU with Ceramic Bead	Dimensional Stability	EN 434	≤ 0,08%
Embossing	Satin	Color Fastness toLight	EN 20105-B02	≥ 6
Bevelled	yes	Slip Resistance	DIN 51130	R10
Fiberglass	yes	Watertightness	EN 13553	No Penetration
Plank Size	304 x 605 mm	Wear Resistance	EN 660-2	Group T
Sqm per Plank / Pack	0.184 m ² / 1.84 m ²	Antimicrobial Activity	ASTM G 21-96	Class 0
Pallet Packing	73.6 m ² / 40 packs	Fire Rating	EN ISO 9239-1	Bfl - S1
Planks per Pack	10 planks	Warranty for Domestic use		25 Years
Net Wt/Gross Wt per Pallet	750 kg / 800 kg	Warranty for Commercial use		10 Years

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards. Easylock itself can be completely recycled.

- allure Locking brings the versatility and natural look of Stone 1 collection, a state-of-the-art innovative LVT resilient flooring product.
 - allure Locking offers the benefits of simple, no glue installation with no requirement of underlay or heavy tools, making it cheaper, quicker and cleaner to install.
 - Completely waterproof, allure Locking is also warm and quiet underfoot. The product is durable and hygienic, making it suitable for retail, office, hospitality, leisure and residential purposes.
 - The first Locking system to be launched in the resilient flooring industry, allure Locking has a proven track record of successful installations and durability.
- **allure Locking is produced with 100% pure virgin PVC, with all quality and health aspects under strict control.**
 - **Completely recyclable because there are no glue residues or contaminants, allure Locking can also be dismantled and reinstalled, making it the perfect environmentally sustainable product.**

